

CYLINDER LENGTHS

U.S. Units

Part Number	Nominal Capacity (ft³)	Nominal Diameter (in)	Height Outlet (in)	Valve Type	Outlet thread valve
ST227M1U FK-1	0,04	3,15	12,64	RGS-MAN-12-ST1	W21.8x1/14"
ST227M2UFV-1	0,07	3,94	14,96	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-2	0,07	3,94	15,12	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2U FK-1	0,07	4,33	11,97	RGS-MAN-12-ST1	W21.8x1/14"
ST227M2UFJ-1	0,10	4,25	17,72	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFJ-2	0,10	4,25	17,87	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-1	0,10	3,94	18,70	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-2	0,10	3,94	18,70	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-3	0,10	3,94	18,86	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-4	0,10	3,94	18,86	RGS-MAN-12-2FD	W21.8x1/14"
ST227M3U FK-1	0,11	4,33	16,38	RGS-MAN-12-ST1	W21.8x1/14"
ST227M4UFJ-1	0,17	4,25	28,15	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-4	0,17	4,25	28,31	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-3	0,17	5,51	18,50	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-6	0,17	5,51	18,66	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-2	0,17	5,51	18,70	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-5	0,17	5,51	18,86	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-2	0,17	5,51	17,56	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-3	0,17	5,51	17,56	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-5	0,17	5,51	17,72	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-6	0,17	5,51	17,72	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-1	0,17	4,53	23,96	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-4	0,17	4,53	24,11	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-1	0,21	6,00	0,98	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-2	0,21	6,00	1,14	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-3	0,21	6,00	1,65	RGS-MAN-20ST	3/4" BSP
ST227M6U FK-1	0,21	6,02	17,99	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6U FK-3	0,21	6,02	17,99	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6U FK-5	0,21	6,02	17,99	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6UFJ-3	0,24	5,51	23,62	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFJ-4	0,24	5,51	23,78	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFJ-6	0,24	5,51	24,29	RGS-MAN-20ST	3/4" BSP
ST227M6UFJ-1	0,24	5,51	23,62	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFJ-2	0,24	5,51	23,78	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFJ-5	0,24	5,51	24,29	RGS-MAN-20ST	3/4" BSP
ST227M6UFV-1	0,24	5,51	23,58	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-3	0,24	5,51	23,58	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-2	0,24	5,51	23,74	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-4	0,24	5,51	23,74	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-5	0,24	5,51	24,25	RGS-MAN-20ST	3/4" BSP
ST227M6UFV-6	0,24	5,51	24,25	RGS-MAN-20ST	3/4" BSP
ST227M9UFM-3	0,32	7,00	0,98	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-4	0,32	7,00	0,98	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-5	0,32	7,00	1,14	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-6	0,32	7,00	1,14	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-1	0,32	7,00	1,65	RGS-MAN-20ST	3/4" BSP
ST227M9UFM-2	0,32	7,00	1,65	RGS-MAN-20ST	3/4" BSP

Part Number	Nominal Capacity (ft³)	Nominal Diameter (in)	Height Outlet (in)	Valve Type	Outlet thread valve
ST227M12UFM-1	0,42	10,00	0,98	RGS-MAN-12-2FD	3/4" BSP
ST227M12UFM-2	0,42	10,00	1,14	RGS-MAN-12-2FD	3/4" BSP
ST227M12UFM-3	0,42	10,00	1,65	RGS-MAN-20ST	3/4" BSP
ST227M12UFK-1	0,42	7,13	23,19	RGS-MAN-12-ST1	3/4" BSP
ST227M12UFK-3	0,42	7,13	23,19	RGS-MAN-20ST	3/4" BSP
ST227M12UFK-4	0,42	7,13	23,19	RGS-MAN-12-ST1	3/4" BSP
ST227M12UFK-6	0,42	7,13	23,19	RGS-MAN-20ST	3/4" BSP
ST227M13UFAA-1	0,46	9,65	15,75	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFAA-2	0,46	9,65	15,91	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFAA-3	0,46	9,65	16,42	RGS-MAN-20ST	3/4" BSP
ST227M13UFB-2	0,47	7,99	24,02	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFB-4	0,47	7,99	24,02	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFB-6	0,47	7,99	24,69	RGS-MAN-20ST	3/4" BSP
ST227M13UFJ-1	0,47	8,03	23,82	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFJ-2	0,47	8,03	23,82	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFJ-3	0,47	8,03	24,49	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-3	0,47	8,03	22,64	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-4	0,47	8,03	22,80	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-8	0,47	8,03	23,31	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-1	0,47	5,51	42,91	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-2	0,47	5,51	43,07	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-7	0,47	5,51	43,58	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-5	0,47	8,03	23,43	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-6	0,47	8,03	23,58	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-9	0,47	8,03	24,09	RGS-MAN-20ST	3/4" BSP
ST227M16UFM-4	0,57	10,00	19,05	RGS-MAN-12-2FD	3/4" BSP
ST227M16UFM-6	0,57	10,00	19,20	RGS-MAN-12-2FD	3/4" BSP
ST227M16UFM-2	0,57	10,00	19,72	RGS-MAN-20ST	3/4" BSP
ST227M21UFM	0,74	12,01	1,65	RGS-MAN-20ST	3/4" BSP
ST227M25UFAA	0,88	11,81	19,80	RGS-MAN-20ST	3/4" BSP

NOTE: These lengths are approximately due to the differences made in the manufacturing process.

S. I. Units

Part Number	Nominal Capacity (liters)	Nominal Diameter (mm)	Height Outlet (mm)	Valve Type	Outlet thread valve
ST227M1UFK-1	1	80	321	RGS-MAN-12-ST1	W21.8x1/14"
ST227M2UFV-1	2	100	380	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-2	2	100	384	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFK-1	2	110	304	RGS-MAN-12-ST1	W21.8x1/14"
ST227M2UFJ-1	2,7	108	450	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFJ-2	2,7	108	454	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-1	2,7	100	475	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-2	2,7	100	475	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-3	2,7	100	479	RGS-MAN-12-2FD	W21.8x1/14"
ST227M2UFV-4	2,7	100	479	RGS-MAN-12-2FD	W21.8x1/14"
ST227M3UFK-1	3	110	416	RGS-MAN-12-ST1	W21.8x1/14"
ST227M4UFJ-1	4,7	108	715	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-4	4,7	108	719	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-3	4,7	140	470	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-6	4,7	140	474	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-2	4,7	140	475	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFJ-5	4,7	140	479	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-2	4,7	140	446	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-3	4,7	140	446	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-5	4,7	140	450	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-6	4,7	140	450	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-1	4,7	115	608,5	RGS-MAN-12-2FD	W21.8x1/14"
ST227M4UFV-4	4,7	115	612,5	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-1	6	152,4	25	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-2	6	152,4	29	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFM-3	6	152,4	42	RGS-MAN-20ST	3/4" BSP
ST227M6UFK-1	6	153	457	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6UFK-3	6	153	457	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6UFK-5	6	153	457	RGS-MAN-12-ST1	W21.8x1/14"
ST227M6UFJ-3	6,7	140	600	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFJ-4	6,7	140	604	RGS-MAN-12-2FD	W21.8x1/14"
ST227M6UFJ-6	6,7	140	617	RGS-MAN-20ST	3/4" BSP
ST227M6UFJ-1	6,7	140	600	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFJ-2	6,7	140	604	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFJ-5	6,7	140	617	RGS-MAN-20ST	3/4" BSP
ST227M6UFV-1	6,7	140	599	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-3	6,7	140	599	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-2	6,7	140	603	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-4	6,7	140	603	RGS-MAN-12-2FD	3/4" BSP
ST227M6UFV-5	6,7	140	616	RGS-MAN-20ST	3/4" BSP
ST227M6UFV-6	6,7	140	616	RGS-MAN-20ST	3/4" BSP
ST227M9UFM-3	9	177,8	25	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-4	9	177,8	25	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-5	9	177,8	29	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-6	9	177,8	29	RGS-MAN-12-2FD	3/4" BSP
ST227M9UFM-1	9	177,8	42	RGS-MAN-20ST	3/4" BSP
ST227M9UFM-2	9	177,8	42	RGS-MAN-20ST	3/4" BSP
ST227M12UFM-1	12	254	25	RGS-MAN-12-2FD	3/4" BSP

Part Number	Nominal Capacity (liters)	Nominal Diameter (mm)	Height Outlet (mm)	Valve Type	Outlet thread valve
ST227M12UFM-2	12	254	29	RGS-MAN-12-2FD	3/4" BSP
ST227M12UFM-3	12	254	42	RGS-MAN-20ST	3/4" BSP
ST227M12UFK-1	12	181	589	RGS-MAN-12-ST1	3/4" BSP
ST227M12UFK-3	12	181	589	RGS-MAN-20ST	3/4" BSP
ST227M12UFK-4	12	181	589	RGS-MAN-12-ST1	3/4" BSP
ST227M12UFK-6	12	181	589	RGS-MAN-20ST	3/4" BSP
ST227M13UFAA-1	13	245	400	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFAA-2	13	245	404	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFAA-3	13	245	417	RGS-MAN-20ST	3/4" BSP
ST227M13UFB-2	13,4	203	610	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFB-4	13,4	203	610	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFB-6	13,4	203	627	RGS-MAN-20ST	3/4" BSP
ST227M13UFJ-1	13,4	204	605	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFJ-2	13,4	204	605	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFJ-3	13,4	204	622	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-3	13,4	204	575	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-4	13,4	204	579	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-8	13,4	204	592	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-1	13,4	140	1090	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-2	13,4	140	1094	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-7	13,4	140	1107	RGS-MAN-20ST	3/4" BSP
ST227M13UFV-5	13,4	204	595	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-6	13,4	204	599	RGS-MAN-12-2FD	3/4" BSP
ST227M13UFV-9	13,4	204	612	RGS-MAN-20ST	3/4" BSP
ST227M16UFM-4	16	254	483,8	RGS-MAN-12-2FD	3/4" BSP
ST227M16UFM-6	16	254	487,8	RGS-MAN-12-2FD	3/4" BSP
ST227M16UFM-2	16	254	500,8	RGS-MAN-20ST	3/4" BSP
ST227M21UFM	21	305	42	RGS-MAN-20ST	3/4" BSP
ST227M25UFAA	25	300	503	RGS-MAN-20ST	3/4" BSP

NOTE: These lengths are approximately due to the differences made in the manufacturing process.

WARNING: This device is manufactured and approved to be used in fixed extinguishing installations with HFC-227ea. These products are not designed for other use or purpose. If product user has any doubt regarding the application or product use, please contact +34 947 28 11 08. Every not approved use or application or / and any other not approved modification of the product or its function may cause serious accidents or / and personal damages. SIEX 2001 is not responsible for any non-approved use of the application.

IMPORTANT: SIEX 2001 reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.